FR1001CT THRU FR1007CT

GLASS PASSIVATED FAST RECOVERY RECTIFIER

康 比 電 子
HORNBY ELECTRONIC


REVERSE VOLTAGE: **50 to 1000 VOLTS**

FORWARD CURRENT: **10.0 AMPERE**

FEATURES

· Low forward voltage drop
· High current capability
· High capability
· High surge current capability

TO-220



Dimensions in inches and (millimeters)

MECHANICAL DATA

Case: Molded plastic, TO-220
Epoxy: UL 94V-O rate flame retardant
Terminals: Leads solderable per MIL-STD-202 method 208 guaranteed
Polarity: As marked
Mounting position: Any
Weight: 0.08ounce, 2.24gram

Maximum Ratings and Electrical Characteristics

Ratings at 25℃ ambient temperature unless otherwise specified.
Single phase, half wave, 60H_Z, resistive or inductive load.
For capacitive load, derate current by 20%.

	Symbols	*FR1001CT*	*FR1002CT*	*FR1003CT*	*FR1004CT*	*FR1005CT*	*FR1006CT*	*FR1007CT*	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	**Volts**
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	**Volts**
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	**Volts**
Maximum Average Forward Rectified Current See Fig. 2	$I_{(AV)}$	10.0							**Amp**
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	125							**Amp**
Maximum Forward Voltage at 5.0A DC and 25℃	V_F	1.3							**Volts**
Maximum Reverse Current at T_C=25℃	I_R	5.0							**uAmp**
at Rated DC Blocking Voltage T_C=125℃		100							
Typical Thermal Resistance (Note 1)	$R_{\theta JC}$	3							℃/W
Maximum Reverse Recovery Time (Note 2)	T_{RR}	150				250	500		**nS**
Operating and Storage Temperature Range	T_J, Tstg	-55 to +150							℃

NOTES:

1- Thermal Resistance from Junction to Case per Leg Mounted on Heatsink.

2- Reverse Recovery Test Conditions：I_F=.5A，I_R=1A，I_{RR}=.25A.

FR1001CT THRU FR1007CT

GLASS PASSIVATED FAST RECOVERY RECTIFIER

康 比 電 子
HORNBY ELECTRONIC

RATINGS AND CHARACTERISTIC CURVES

FIG.1- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM




FIG.2- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.3- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER LEG




FIG.4- TYPICAL JUNCTION CAPACITANCE PER LEG




FIG.5- TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG.6- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER LEG

