SR2020PT THRU SR20200PT

SCHOTTKY BARRIER RECTIFIER

康 比 電 子
HORNBY ELECTRONIC


REVERSE VOLTAGE: **20 to 200 VOLTS**

FORWARD CURRENT: **20.0 AMPERE**

FEATURES

- Plastic package has UL flammability classification 94V-0
- Metal of silicon rectifier,majority carrier conduction
- Guard ring for transient protection
- High capability
- Low power loss, high efficiency
- High current capability, low V_F
- High surge capacity
- For use in low voltage,high frequency inverters,free whelling,and polarity protection applications

TO-3P/TO-247AD



Dimensions in inches and (millimeters)

MECHANICAL DATA

Case: Molded plastic, TO-3P/TO-247AD
Epoxy: UL 94V-O rate flame retardant
Terminals: Leads solderable per MIL-STD-202 method 208 guaranteed
Polarity: As marked
Mounting position: Any
Weight: 0.2ounce, 5.6gram

Maximum Ratings and Electrical Characteristics

Ratings at 25℃ ambient temperature unless otherwise specified.
Single phase, half wave, 60H_Z, resistive or inductive load.
For capacitive load, derate current by 20%.

	Symbols	*SR2020PT*	*SR2030PT*	*SR2040PT*	*SR2050PT*	*SR2060PT*	*SR2080PT*	*SR20100PT*	*SR20150PT*	*SR20200PT*	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	20	30	40	50	60	80	100	150	200	**Volts**
Maximum RMS Voltage	V_{RMS}	14	21	28	35	42	56	70	105	140	**Volts**
Maximum DC Blocking Voltage	V_{DC}	20	30	40	50	60	80	100	150	200	**Volts**
Maximum Average Forward Rectified Current See Fig. 1	$I_{(AV)}$	20.0									**Amp**
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	250									**Amp**
Maximum Forward Voltage at 10.0A DC and 25℃ (Note 3)	V_F	0.55			0.70		0.85		0.95		**Volts**
Maximum Reverse Current at T_C=25℃	I_R	1.0							0.2		**mAmp**
at Rated DC Blocking Voltage T_C=100℃		50									
Typical Junction Capacitance (Note 1)	C_J	600			400						**pF**
Typical Thermal Resistance (Note 2)	$R_{\theta JC}$	2.0									**℃/W**
Operating Temperature Range	T_J	-55 to +125			-55 to +150						**℃**
Storage Temperature Range	Tstg	-55 to +150									**℃**

NOTES:

1- Measured at 1 MH_Z and applied reverse voltage of 4.0 VDC.
2- Thermal Resistance from Junction to Case Per Leg
3- 300 us Pulse Width, 2% Duty Cycle

SR2020PT THRU SR20200PT

SCHOTTKY BARRIER RECTIFIER

康比電子 HORNBY ELECTRONIC

RATINGS AND CHARACTERISTIC CURVES

FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER LEG




FIG.5- TYPICAL JUNCTION CAPACITANCE PER LEG




FIG.3- TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG.4- TYPICAL FORWARD CHARACTERISTICS

